



<b>Grade</b>	JH-370A
<b>Product</b>	PP

### General Information

Key Features - Impact resistance, Slipperiness

Applications Industrial/Household goods, Home appliances, PP Compound Base Resin

Item	Measuring Method	Unit	Value
<b>Physical</b>			
Melt Flow Index	ASTM D1238	g/10min	27.0
Density	ASTM D1505	g/cm <sup>3</sup>	0.9
<b>Mechanical</b>			
Tensile Stress (Yield)	ASTM D638	kgf/cm <sup>2</sup>	230
Tensile Strain (Break)	ASTM D638	%	≥100
Flexural Modulus	ASTM D790	kgf/cm <sup>2</sup>	12,500
<b>Impact</b>			
Izod Impact Strength(notched) (23°C)	ASTM D256	kgf·cm/cm	10.0
Izod Impact Strength(notched) (-10°C)	ASTM D256	kgf·cm/cm	5.0
<b>Thermal</b>			
Heat Deflection Temperature(4.6kgf/cm <sup>2</sup> )	ASTM D648	°C	105
<b>Additional Properties</b>			
Flammability	UL94		HB

1. Physical Properties : these are not to be construed as specifications
2. ISO 9001, 14001, /TS 16949

\* The last update date : 2021/10/01