



Grade	L-270A
Product	PP

General Information

Key Features
L-270A is designed to potential end use applicatic coating on Woven and Kraft Paper. Low neck-in, High speed processability, good adh paper, Oil & moisture permeation resistance.

Applications
Resin, fish, steel, tube dog food packaging

Item	Measuring Method	Unit
Physical		
Melt Flow Index	ASTM D1238	g/10min
Density	ASTM D792	g/cm ³
Mechanical		
Tensile Stress (Yield)	ASTM D638	kgf/cm ²
Tensile Strain (Break)	ASTM D638	%
Flexural Modulus	ASTM D790	kgf/cm ²
Rockwell Hardness	ASTM D785	R
Impact		
Izod Impact Strength(notched) (23°C)	ASTM D256	kgf·cm/cm
Thermal		
Melting Temperature	ASTM D3418	°C
VICAT Softening Temperature	ASTM D1525	°C
Heat Deflection Temperature(4.6kgf/cm ²)	ASTM D648	°C

1. Physical Properties : these are not to be construed as specifications
2. ISO 9001, 14001, /TS 16949

* The last update date : 2021/10/01

[Redacted]

on include Extrusion

esive property to

Value
26.0
0.9
290
≥500
13,000
99
3.7
162
149
105