

<b>Grade</b>	SEP-750
<b>Product</b>	PP

### General Information


Key Features - Heat adhesion, impact resistance, softness,

Applications EPP (acoustic absorber, Packaging)

Item	Measuring Method	Unit
<b>Physical</b>		
Melt Flow Index	ASTM D1238	g/10min
Density	ASTM D1505	g/cm <sup>3</sup>
<b>Mechanical</b>		
Tensile Stress (Yield)	ASTM D638	kgf/cm <sup>2</sup>
Tensile Strain (Break)	ASTM D638	%
Flexural Modulus	ASTM D790	kgf/cm <sup>2</sup>
<b>Impact</b>		
Izod Impact Strength(notched) (23°C)	ASTM D256	kgf·cm/cm
Izod Impact Strength(notched) (-10°C)	ASTM D256	kgf·cm/cm
<b>Thermal</b>		
Heat Deflection Temperature(4.6kgf/cm <sup>2</sup> )	ASTM D648	°C
<b>Additional Properties</b>		
Flammability	UL94	

1. Physical Properties : these are not to be construed as specifications
2. ISO 9001, 14001, /TS 16949

\* The last update date : 2021/10/01



elasticity

---

Value
7.0
0.9
220
>100
7,500
10.0
2.5
115
HB

---